

Sanyo Denki - BL Super Servo Amplifiers

RBD2A-205



<table-of-contents> Request a Quote

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



Free Ground Shipping One Year Warranty

16 (24 VDC

The **RBD2A-205** is a part of the **BL Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Communication cycle	2-16 ms	Cooling method:	Passive cooling	Digital inputs:	common)
Digital outputs:	8 (19.2-30 VDC, 0.5 A each)	Dimensions:	55×120×110 mm	EtherCAT interface:	100 Mbps
Ethernet interface:	10/100/1000 Mbps	Humidity (op/storage):	10-95% RH non- condensing	I/O power supply:	24 VDC (19.2-30 VDC), 20 mA
Main power supply:	24 VDC (19.2-30 VDC), 0.8 A	Mass:	300 g	Max controllable axes:	8
	19.2 W	DC 405 interfece	9600-115200 bps		147 m/s^2 peak, 11 ms (JIS B
Power consumption:		RS-485 interface:	06/05/2025	Shock resistance:	3502:2011)
USB interface:	USB 2.0	Last Verified:	2:48 AM		

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.