



Sanyo Denki - K SANMOTION Servo Motors

KA406TXX



In Stock, Shipping Varies

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **KA406TXX** is a part of the **K SANMOTION Servo Motors Series** by **Sanyo Denki**.

Specifications

Ambient Operating Temperature:	0 to 40°C	Armature Inductance:	4.5 mH Standard: 2000 P/R (Optional: 200, 500, 1000 P/R)	Armature Winding Resistance:	9.8 ?
Continuous Stall Torque:	0.20 N·m	Encoder Pulses Per Revolution:		Peak Stall Torque:	1.2 N·m
Protection Rating:	IP43	Rated Armature Voltage:	70 V	Rated Output:	60 W
Rated Speed:	3000 min ⁻¹	Rated Torque:	0.19 N·m	Rotor Inertia:	0.108 × 10 ⁻⁴ kg·m ²
Torque Constant:	0.177 N·m/A	Voltage Constant:	18.5 × 10 ⁻³ V/min ⁻¹	Last Verified:	05/08/2025 4:58 PM

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.