

Sanyo Denki - P3 Super BL Servo Motors**P30B04010P XKST** **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer

Secure Online
CheckoutFree Ground
ShippingOne Year
Warranty

The **P30B04010P XKST** is a part of the **P3 Super BL Servo Motors Series** by **Sanyo Denki**.

Specifications

Ambient Humidity:	20 to 90% (non-condensing)	Dielectric Strength:	1,500 VAC for 1 minute	Installation Method:	Flange mounting
Insulation Grade:	F type	Insulation Resistance:	500 VDC, ?10 M?	Maximum Rotating Speed:	Up to 4,500 min? ¹
Operating Voltage:	200 to 230 VAC ($\pm 10\%$ /-15%), 50/60Hz	Paint Color:	Munsell N1.5 or equivalent	Phase armature resistance:	4.3 ?
Protection Rating:	Fully closed, self-cooling, IP40	Rated power:	0.1 kW	Rated Rotating Speed:	Approximately 3,000 min? ¹
Rated Torque:	0.32 Nm	Time Rating:	Continuous	Vibration Grade:	V15
Last Verified:	07/10/2025 6:11 PM				

Contact Us 1620 Old Apex Road, Cary, NC 27513, USA Toll Free: [1-888-551-3082](tel:1-888-551-3082) International: [1-919-443-0207](tel:1-919-443-0207) Fax: [1-919-867-6204](tel:1-919-867-6204) Email: sales@automation-factory.com**Shipping Options****Payment Methods**

Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.