



Sanyo Denki - P3 Super BL Servo Motors

P30B06020DCL76



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **P30B06020DCL76** is a part of the **P3 Super BL Servo Motors Series** by **Sanyo Denki**.

Specifications

Ambient Humidity:	20 to 90% (non-condensing)	Backlash:	90 arcmin	Brake Type:	C-Brake (24 V DC)
Dielectric Strength:	1500 VAC, 1 min	Flange Angle Dimension:	76 mm	Instantaneous Max Torque:	25.2 N·m
Insulation Class:	Class F	Motor Output:	200 W	Protection System:	Fully closed, self-cooling, IP40
Rated Torque:	8.6 N·m	Reduction Ratio:	1:15	Storage Temperature:	-20 to +65 °C
Time Rating:	Continuous	Last Verified:	07/11/2025 6:19 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.