

Sanyo Denki - P5 Super BL Servo Motors

P50B08100HCS500E



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



Checkout

Free Ground Shipping

One Year Warranty

The **P50B08100HCS500E** is a part of the **P5 Super BL Servo Motors Series** by **Sanyo Denki**.

Specifications

Ambient Operating Humidity:	20 90% non? condensing	Ambient Operating Temperature:	0₅₅40 °C	Brake Excitation Current:	0.08 A (0.33 A opt)
Brake Excitation Voltage:	90 V (24 V opt)	Continuous Stall Armature Current:	7.5 Arms	Dielectric Strength:	1,500 VAC, 1 min
Encoder Resolution:	2,000 pulses/rev (opt 8,192)	Installation Method:	Flange; permanent magnet excitation	Instantaneous Stall Torque:	11.76 N·m
Insulation Class:	F type	Insulation Resistance:	?10 M? @500 VDC	Maximum Rotating Speed:	4,500 rpm
Protection System:	Fully closed, self? cooling IP55	Rated Armature Current:	6.7 Arms	Rated Power:	1,000 W
Rated Rotating Speed:	3,000 rpm	Rated Torque:	3.185 N⋅m	Last Verified:	07/03/2025 12:35 PM

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.