

Sanyo Denki - PM Drivers

PMDPC1C3P50-A1



 **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PMDPC1C3P50-A1** is a part of the **PM Drivers Series** by **Sanyo Denki**.

Specifications

Conservation humidity temperature:	10 to 90 percent	Conservation temperature:	-20 to 70 degrees	Control Mode:	Servo control (closed-loop)
Cooling Method:	Fan-cooled or natural convection	Efficiency:	Typically >85%	Environmental Specs:	Operating temperature -10°C to +60°C, 5-95% RH
Input Voltage Range:	1-24 V DC (typical)	Insulation resistance:	10 MegaOhms	LED indicator:	Alarm Monitor
Operating ambient humidity:	35 to 85 percent	Operating ambient temperature:	0 to 50 degrees	Operating Frequency Range:	20 kHz to 100 kHz (typical range)
Protection Features:	Overload, short-circuit, and thermal protection	Rated Output Power:	50 W (approx.)	Vibration resistance:	1.9m/s2
Last Verified:	07/09/2025 1:25 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

