

Sanyo Denki - PM Drivers

PMDSA1S3P01



 **In Stock, Ships Fast**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PMDSA1S3P01** is a part of the **PM Drivers Series** by **Sanyo Denki**.

Specifications

Applicable Driver:	Photo coupler input	Connector:	VHR-3N (Terminal: SVH-21T-P1.1)	Holding Torque (2-phase Energization):	0.44 N·m (62.31 oz·in)
Insulation Resistance:	Not less than 100 M Ω (by DC500V megger)	Lead Wire Type:	UL1430 AWG22	Mass (other Configuration):	0.65 kg (1.43 lbs)
Operational Temperature:	-10 to +50°C	Power Source Voltage:	DC24V	Pulse Interface:	DC power input
Rated Current:	3 A/phase	Rotor Inertia:	0.12 x10 ⁻⁴ kg·m ² (0.66 oz·in ²)	Stepper Motor Compatibility:	3-phase, 50mm sq. (1.97 inch sq.)
Weight:	0.5 kg (1.10 lbs)	Winding Inductance:	1.6 mH/phase	Wiring Resistance:	1.3 Ω /phase
Last Verified:	12/13/2025 10:47 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

