

Sanyo Denki - PM Drivers

PMM-BA-4804-1



 **In Stock, Ships in 3-5 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PMM-BA-4804-1** is a part of the **PM Drivers Series** by **Sanyo Denki**.

Specifications

Alarm Monitor:	Relay contact output (DC24V, 0.5A or less)	Automatic Current Down Feature:	Selectable	Conservation Temperature:	-20~+70°C
Getaway Torque:	15.1x10-4kg-m2 (rubber coupling)	Input Signal Voltage (cw/ccw):	H = 4.0 to 5.5V, L = 0 to 0.5V	Insulation Resistance:	10MΩ or more (DC500V)
Max Input Frequency:	100kpulse/s	Operating Ambient Humidity:	35~85% RH (no condensation)	Operating Ambient Temperature:	0~+50°C
Power Down Function:	Enabled by signal input	Protection Function:	Against PM driver overheat	Rated Current:	6A/phase (Changeable to 4A/phase)
Source Voltage:	AC100V	Vibration Resistance:	4.9m/s ² (10~55Hz frequency range)	Wire-wound Current:	6A/phase
Last Verified:	05/09/2025 2:38 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.