

Sanyo Denki - PM Drivers

PMM-MD-23220-10



 **In Stock, Ships 2-3 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping




One Year
Warranty

The **PMM-MD-23220-10** is a part of the **PM Drivers Series** by **Sanyo Denki**.

Specifications

Ambient Humidity Range For Operation:	35~85% (non-condensing)	Ambient Humidity Range For Storage:	10~90% (non-condensing)	Dimensions:	Refer to driver and mechanical specs sections
Driver Current Settings:	Set via switch from rated current to 0%	Input Resistance For Photo Coupler:	330?	Input Signal Voltage (h):	4.0 to 5.5V
Input Signal Voltage (l):	0 to 0.5V	Insulation Resistance:	10 Mega Ohms	Maximum Input Frequency:	100kpulse/s
Protection Function:	Against PM driver overheat 4.9m/s ² (10 ⁵ SPR) 55Hz along X, Y, Z axes for 2 hours each)	Rated Current:	2A/phase	Source Voltage:	DC24V
Vibration Resistance:		Weight:	0.6 kg	Last Verified:	05/10/2025 4:05 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.