

Sanyo Denki - PM Drivers

PMM-UA-4304-1



 **In Stock, Ships Fast**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PMM-UA-4304-1** is a part of the **PM Drivers Series** by **Sanyo Denki**.

Specifications

Alarm Output Signal:	Relay contact, DC24V 0.5A or AC120V 0.5A	Coupling Type:	Rubber coupling	Input Voltage & Frequency:	Single-phase AC100V ±10%, 50/60Hz ±3Hz
Max Input Pulse Frequency:	20 kpps	Operating Ambient Humidity:	35% to 85% RH (no condensation)	Operating Ambient Temperature:	0 to +50 °C
Phase Current Setting:	3.6, 4, 4.6, 5 A/phase	Protection Functions:	Overheat monitor, Alarm output	Rotation Control:	CW & CCW pulse input
Rotor Inertia:	15.1×10 ⁻⁴ kg·m ²	Step Mode:	Full-step / Half-step (200 / 400 steps)	Storage Temperature:	-20 to +70 °C
Vibration Resistance:	4.9 m/s ² , 10 ⁵ Hz, X/Y/Z axes, 2h each	Weight:	3 kg	Last Verified:	05/10/2025 3:30 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.