

Sanyo Denki - PV Super Servo Amplifiers

PV2A015SMT1PA0-C1



Complian with

♣ In Stock, Ships in 3-5 Days

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



Checkout

Free Ground Shipping



The **PV2A015SMT1PA0-C1** is a part of the **PV Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Compliance & Standards:	industrial safety and EMC standards	Control Mode:	Closed-loop servo control	Cooling Method:	Forced air
Stanuarus.	Stanuarus	Control would.		Cooling Method.	Digital with
Dimensions:	Compact size	Efficiency:	> 90%	Feedback Type:	encoder integration
	High-frequency	-	Typically		PCB or rack-
Frequency Response	: performance	Input Voltage:	200 5Pm 240 V AC	Mounting Type:	mountable
Operating Environment:	Suitable for industrial conditions, -10°C to +55°C	Output Current:	Approximately 15 A	Output Voltage:	Typically 24VDC or comparable range
Product Category:	Servo Amplifier	Protection Features:	Overcurrent, overvoltage, and thermal protection	Signal Interface:	Digital control signals such as RS422/RS485
Last Verified:	07/03/2025 10:21 PM		·	-	

Contact Us

- 9 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.