

Sanyo Denki - PV Super Servo Amplifiers

PV2A015SMT1PA0-C2



 **In Stock, Ships in 3-5 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PV2A015SMT1PA0-C2** is a part of the **PV Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Ambient Temperature Range:	0 to 40°C	Communication Interface:	RS-485 or fieldbus option available	Compliance And Certifications:	Meets CE and UL standards (if applicable)
Connectors:	CN1, CN2, CN3, CN4, CN5, CN6	Cooling Method:	Fan-cooled	Environmental Protection:	Typically IP20 (industrial enclosure)
Estimated Power Rating:	Around 2 kW (typical for this series)	Input Voltage Range:	Typically 200-480 V (depending on configuration)	Installation:	Panel mount design
Mounting Style:	DIN rail or panel-mountable	Overload Capacity:	Up to 150% short-term overload capability	Protection Features:	Overcurrent, Overvoltage, and Overtemperature protection
Rated Output Current:	Approximately 15 A (inferred from model code)	Storage Temperature Range:	-20 to 65°C	Switching Frequency:	Approximately 10 kHz (typical value)
Last Verified:	07/03/2025 10:39 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

