



Sanyo Denki - PV Super Servo Amplifiers

PV2A015WN31A0Y



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PV2A015WN31A0Y** is a part of the **PV Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Communication Interface:	SERCOS interface	Connector CN2:	High?density D? sub	Connector CN4:	Power/Signal
Connector CN5:	Terminal block	Connectors:	CN1, CN3	Dimensions:	10 × 10 × 2 mm
Efficiency:	95%	ESD Protection:	±2 kV	Input Capacitance:	10 μF
Isolation Voltage:	3000 V	Maximum Voltage:	200 V	Mounting Type:	Surface?mount
Nominal Current:	15 A	Operating Temperature Range:	−40 °C to 125 °C	Output Capacitance:	47 μF
Power Loss:	0.5 W	Switching Frequency:	100 kHz	Thermal Resistance:	50 °C/W
Last Verified:	07/03/2025 5:27 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.