

Sanyo Denki - PY Super BL Servo Amplifiers

PY2A050E4XXYPH3



 **In Stock, Ships Fast**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PY2A050E4XXYPH3** is a part of the **PY Super BL Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Ambient operating temperature:	0°C to 55°C.	Control circuit power input:	Single-phase 200 ^{SFR} 230 VAC (+10%/-15%), 50/60 Hz ±3 Hz	Control function:	Velocity, torque or position control.
Depth:	135 mm.	Electrical protection functions:	Overcurrent, overload, power & sensor errors.	Height:	168 mm (excl. mounting fittings).
High-voltage I/O wiring:	Connector-type terminals.	Main circuit power input:	Three-phase 200 ^{SFR} 230 VAC (+10%/-15%), 50/60 Hz ±3 Hz	Mass:	~2.7 kg.
Operating/storage humidity:	Up to 90% RH (no condensation). 1:5000 speed ratio.	Storage temperature:	20°C to 65°C.	Thermal and speed protection:	Overheat, overspeed. 07/05/2025 2:33 PM
Velocity control range:		Vibration tolerance:	0.5 G, 10 ^{SFR} 55 Hz, 2 h, XYZ axes.	Last Verified:	

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.