

#### Sanyo Denki - R SANMOTION Servo Drives

# RS2A03A0AA0



<table-of-contents> In Stock, Ships 2-3 Days

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



Free Ground Shipping One Year Warranty

The **RS2A03A0AA0** is a part of the **R SANMOTION** Servo Drives Series by Sanyo Denki.

## Specifications

Amplifier Mass:	0.9 kg	Amplifier Operating Temperature:	0 to 55°C	Amplifier Power Supply:	AC200V to 230V ±10%
Brake Mass:	0.27 kg	Brake Rated Current:	0.07 / 0.27 A	Brake Rated Voltage:	DC90V / DC24V ±10%
Brake Static Friction Torque:	0.32 N·m minimum	Encoder Connection Type:	Plug 10120- 3000PE and Shell 10320- 52A0-008	Mass Including Encoder:	0.35 kg
Motor Dimensions:	Data available in P24	Motor Operating Temperature:	0 to 40°C	Rated Power Supply:	0.2 kVA
Relative Humidity (motor Operating):	90% max, non- condensing	Rotor Moment Of Inertia (with Encoder)	0.0033 ×10?? kg·m²	Rotor Moment Of Inertia (without Encoder):	0.0247 ×10?? kg⋅m²
Last Verified:	07/01/2025 11:56 AM			·	

### **Contact Us**

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

## **Shipping Options**



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.