

Sanyo Denki - R SANMOTION Servo Drives

RS2A03A2MA3E00



 **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **RS2A03A2MA3E00** is a part of the **R SANMOTION Servo Drives Series** by **Sanyo Denki**.

Specifications

Amplifier Mass:	0.9 kg (single-axis)	Axes Supported:	up to 8 axes per segment	CAN Bus:	ISO-11898 compliant, max 25 m @1Mbps
CANopen Bit Rates:	1, 800, 500, 250, 125, 50, 20, 10 kbps	CANopen Protocol:	CiA DS301 & DS402	Comm Objects:	SDO, EMCY, SYNC, PDO, NMT, Heartbeat
Connector:	RJ-45, 2 ports, 120? terminator option	Control Modes:	Homing, Profile Vel, Torque, Position, Interpolated	Operating Temp:	0°C to 55°C; 0% to 90% RH non-cond.
Output Ports:	8 configurable ports	Output Supply:	5V@10mA, 12V@15V@30mA, 24V@50mA	Protection:	breaker, noise filter, surge prot; ext regen resistor
Rated Power:	0.2 kVA (single), 0.4 kVA (multi)	RS-485 Bit Rates:	4.8SPR115.2 kbps	RS-485 Interface:	Modbus-RTU half?duplex; configurable frame
Last Verified:	06/30/2025 11:29 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.