

Sanyo Denki - R SANMOTION Servo Motors

R2AA2220KBXPG0Y



 [Request a Quote](#)

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **R2AA2220KBXPG0Y** is a part of the **R SANMOTION Servo Motors Series** by **Sanyo Denki**.

Specifications

Aluminum Plate Dimensions:	t6x250 (typical)	Armature Current At Stall:	6.0 Arms (typical)	Brake Mass (w):	0.9 kg (typical)
Continuous Torque At Stall:	0.353 NM (typical)	Mass (we):	2.7 kg (typical)	Peak Armature Current At Stall:	14.1 Arms (typical)
Peak Torque At Stall:	1.5 Nm (typical)	Phase Resistance:	0.51 ? (typical)	Rated Armature Current:	6.0 Arms (typical)
Rated Output:	200 kW (typical)	Rated Power Rate:	35 kW/s (typical)	Rated Torque:	0.637 NM (typical)
Rotor Inertia (jm):	1.653 x 10^-4 kg? m2 (typical)	Torque Constant:	0.607 NM/Arms (typical)	Voltage Constant For Each Phase:	18.9 mV/min-1 (typical)
Last Verified:	06/19/2025 5:37 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.