

Sanyo Denki - SANUPS Power Supplies**ASE15S1U001-20** **In Stock, Ships Today**


- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer


Secure Online
Checkout
Free Ground Shipping
One Year Warrant

The **ASE15S1U001-20** is a part of the **SANUPS Power Supply Series** by Sanyo Denki.

Specifications

Acoustic Noise:	40dB (1 ^{SPR} 1.5kVA);	Backup Time:	~5 min at 3kVA, 120V	Battery:	Maintenance-free sealed lead-acid
	45dB (2 ^{SPR} 3kVA) at 1m				
Certifications:	UL1778 4th Ed, CE, FCC Part15B Class A	Heat Dissipation (120V):	125W@1kVA, 200W@1.5kVA, 250W@2kVA, 410W@3kVA	Heat Dissipation (208V):	125W@1kVA, 270W@2kVA, 450W@3kVA
Input Frequency:	50/60Hz auto-sensing	Input Frequency Tolerance:	±1/±3/±5% normal; ±0.5% battery	Input Phase:	Single-phase, 2-wire
Input Power Factor:	0.7 Econ; ? 0.85 AF; ?0.95 DC	Input Voltage Range by Mode:	Econ ±8%; AF ±5%; DC -20/+15	Operating Humidity:	20 ^{SPR} 90% non-condensing
Operating Temp:	0 ^{SPR} 40°C (32 ^{SPR} 104°F)	Output Frequency:	Synchronous with input	Output Voltage:	Matches input (120V/208V)
Contact Us	120V (1, 1.5, 2, 3kVA); 208V (1, 2, 3kVA)	Voltage Regulation:	Econ ±8%; AF ±5%; DC ±2%	Last Verified:	07/02/2025 12:59 AM

 1620 Old Apex Road, Cary, NC 27513, USA Toll Free: [1-888-551-3082](tel:1-888-551-3082) International: [1-919-443-0207](tel:1-919-443-0207) Fax: [1-919-867-6204](tel:1-919-867-6204) Email: sales@automation-factory.com**Shipping Options****Payment Methods**

Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.