

Sanyo Denki - SANUPS Power Supplies

BP100XX26



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **BP100XX26** is a part of the **SANUPS Power Supplies Series** by Sanyo Denki.

Specifications

Available Ratings at 120V:	1kVA; 1.5kVA; 2kVA; 3kVA
Backup Time (3kVA):	3.5 minutes
Heat Dissipation (120V Models):	1kVA:125W; 1.5kVA:200W; 2kVA:250W; 3kVA:410W
Output Power Ratings:	1kVA(0.7kW); 1.5kVA(1.05kW); 2kVA(1.4kW); 3kVA(2.1kW)
Power Factor (Double Conversion Mode):	?0.95
Voltage Distortion (Linear Load):	?3%
Voltage Regulation (Economy Mode):	+8% Max.

Available Ratings at 208V:	1kVA; 2kVA; 3kVA
Battery Type:	Maintenance Free Sealed Lead-Acid Battery
Heat Dissipation (208V Models):	1kVA:125W; 2kVA:270W; 3kVA:450W
Overcurrent Protection:	1kVA: Fuse; 1.5/2/3kVA: Breaker
Power Factor (Economy Mode):	0.7
Voltage Regulation (Active Filter Mode):	±5% Max.
Last Verified:	08/22/2025 6:18 PM

Backup Time (1kVA, 1.5kVA, 2kVA):	5 minutes
Cooling Method:	Forced Air
Operating Temperature:	0°C to 40°C (32°F to 104°F)
Power Factor (Active Filter Mode):	?0.85
System Topology:	Hybrid
Voltage Regulation (Double Conversion Mode):	±2% Max.

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

