

Sanyo Denki - SANUPS Power Supplies

H-16KW MG



In Stock, Ships Today

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer

Ċ
Secure Online
Checkout

Free Ground Shipping One Year Warranty

The H-16KW MG is a part of the SANUPS Power Supplies Series by Sanyo Denki.

Specifications

AC Input:	Single-phase, 2- wire	Backup Time:	5 min (3 kVA); 3.5 min (120 V)	Battery Type:	Maintenance-free sealed SLA
Capacity:	1sen3 kVA (120 V/208 V)	Cooling Method:	Forced air	Freq. Tolerance (battery):	±0.5% max
Freq. Tolerance (normal):	±1%, ±3%, ±5% selectable	Input Frequency:	60 Hz default, 50/60 Hz auto	Input Voltage Range:	±8% (120 V), ±5% (208 V)
Operating Humidity:	20 90% RH non- condensing	Operating Temp.:	0 ^{sp#} 40 °C (32 ^{sp#} 104 °F)	Output Power Factor	0.7 lagging (alt. ? : 0.85/0.95)
Output Reg. (std):	±8% (120 V), ±5% (208 V)	Output Reg. (tight mode):	±2% max	Overcurrent Protection:	1 kVA fuse; ? 1.5 kVA breaker; bypass auto- return
Safety Compliance:	UL1778-4, CE, FCC Part 15 B Class A	System Topology:	Hybrid UPS (double-conv., economy, active filter)	Last Verified:	07/02/2025 7:18 PM

Contact Us

- 9 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.