



Sanyo Denki - StepSyn Stepping Motors

103H5510-7040



In Stock, Ships in 3-5 Days

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **103H5510-7040** is a part of the **StepSyn Stepping Motors Series** by **Sanyo Denki**.

Specifications

Heat Resistance:	withstand voltage and insulation resistance compliant	Holding Torque:	0.255 N·m (36.11 oz·in)	Humidity Range:	35 to 85% RH (no condensation)
Mass (weight):	0.37 kg (0.82 lbs)	No Load Maximum Starting Pulse Rate:	Available in Full Step and Half Step	Operating Current:	0.75A/phase
Pull-out Torque (24v, J11):	$0.94 \times 10^{-4} \text{ kg} \cdot \text{m}^2$ (5.14 oz·in ²)	Pull-out Torque (36v, J11):	$0.94 \times 10^{-4} \text{ kg} \cdot \text{m}^2$ (5.14 oz·in ²)	Pulse-rate Characteristics:	Pulse rate and torque characteristics documented (kpulse/s)
Rotor Inertia:	$0.065 \times 10^{-4} \text{ kg} \cdot \text{m}^2$ (0.36 oz·in ²)	Source Voltage:	DC24V or DC36V	Step Angle Setting:	Divisible into up to 80 resolutions
Temperature Range (conservation):	-20°C to +70°C	Temperature Range (operation):	0°C to +50°C	Vibration Resistance:	Applicable within 10 to 55 Hz frequency
Last Verified:	06/20/2025 2:04 AM				

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods

