



Vickers - EEA-PAM-5-A-33 Power Amplifiers

EEA-PAM-533-A-33



 **In Stock, Ships 2-3 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **EEA-PAM-533-A-33** is a part of the **EEA-PAM-5-A-33 Power Amplifiers Series** by **Vickers**.

Specifications

Alarm Output Voltage Range:	0 to ± 2 volts	Analog Input Voltage Range:	$\pm 10V$	Deadband Compensation:	0 to 50%
Digital Input Voltage:	17 to 40V for enabled; 0 to 3.5V for disabled	Input Impedance:	47k Ω for voltage inputs, 100 Ω for current inputs	Installation Dimensions:	128.4mm x 175.24mm with 7.92mm pin spacing
Load Impedance For Analog Outputs:	?10k Ω ; short-circuit proof	Mass:	0.4 kg (0.88 lb)	Maximum Solenoid Current:	2.7A for the EEA-PAM-533 model
Operating Temperature Range:	0 to 50°C (32 to 122°F)	Output Ramp Generator Voltage Range:	$\pm 10V$	Power Supply Voltage Range:	20 - 40V (including peak-to-peak ripple 10% max.)
Reference Voltages:	+10V at 5mA and -10V at 5mA	Voltage Range For Analog Outputs:	$\pm 10V$	Last Verified:	05/08/2025 8:09 PM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.